

LMB-650 SERIES







Features

- 1/3" SONY Super HAD CCD
- True Day and Night function
- Audio selectable
- All function switchable
- Dual power sources
- Infrared acceptable
- Ten multi-functions ON/OFF



Dimensions



ITEMS	LMB-650 SERIES
SCANNING SYSTEM	2:1 Interlace
ELECTRONIC SHUTTER	ON/OFF switchable
GAIN CONTROL	ON/OFF switchable
BACK LIGHT COMPENSATION	ON/OFF switchable
WHITE BALANCE	Auto
DAY/NIGHT	ON/OFF Switchable (Optional)
LINE LOCK	Yes (Optional) For AC TYPE
ICR	Yes (Optional)
AUTO IRIS	DC/AI switchable
S/N RATIO	More Than 52 dB
GAMMA	0.45
VIDEO OUTPUT	1 VP-P, 75 ohm
STORAGE/OPERATING TEMPERATURE	-30°C ~ +60°C / -10°C ~ +45°C
DIMENSIONS (L*W*H) mm	105*60*58
WEIGHT	210g

Model NO.	Image Sensor	Picture Elements H*V	TVL	Lens Type	Power Consumption	Sensitivity F:1.2	Chip
LMB-650HQ	1/3" SONY Super HAD CCD	NTSC:768(H)×494(V) PAL:752(H)×582(V)	540	CS Mount	DC12V/120mA AC90V~260V/3W	0.2 LUX	SONY HQ1
LMB-650HQC	1/3" SONY Super HAD CCD	NTSC:768(H)×494(V) PAL:752(H)×582(V)	540	CS Mount	DC12V/120mA AC90V~260V/3.6W	0.05 LUX	SONY HQ1
LMB-650ASR	1/3" SONY CCD	NTSC:512(H)×492(V) PAL:500(H)×582(V)	420	CS Mount	DC12V/90mA	0.1 LUX	SONY 11R
LMB-650AXE	1/3" SONY CCD	NTSC:512(H)×492(V) PAL:500(H)×582(V)	430	CS Mount	DC12V/110mA	0.05 LUX	SONY 11X
LMB-650AXH	1/3" SONY Super HAD CCD	NTSC:768(H)×494(V) PAL:752(H)×582(V)	520	CS Mount	DC12V/110mA	0.05 LUX	SONY 11X